2 AA BATTERIES

XPP-5414GX

INTRINSICALLY SAFE DUAL-LIGHT FLASHLIGHT

NIGHTSTICK®
Life Depends on Light™

CLASS I DIV 1

ATEX ZONE 0 IECEx

IP-67 DUST/WATER PROOF

HANDS-FREE INTEGRATED MAGNET

Dual top-mounted switches.
Easy to use with gloves on.

Powerful rare-earth tail magnets
for additional hands-free use

Unfocused floodlight for close-up illumination



Dustproof/Waterproof (IP-67)
and chemical/heat resistant for any environment

DUAL LIGHT TECHNOLOGY

CERTIFIED

CE | IECEx | Ex | Intertek | NFPA | UK CA 0359

AVAILABLE AS A KIT

120 LUMENS

1-800-233-2155 · 1-469-326-9400 · nightstick.com

© 2023 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

INTRINSICALLY SAFE

PRODUCT SPECIFICATION SHEET

DUAL-LIGHT FLASHLIGHT

2 AA BATTERIES (not included)

FL1 STANDARD	SPOT	FLOOD	DUAL-LIGHT
	120 LUMENS	120 LUMENS	120 LUMENS
	24h	24h	24h
	111m		
	3100cd		
2m			
1m			

Intertek
ID 4003544
INTRINSICALLY SAFE
SECURITE INTRINSEQUE

CE 2575
UK CA 0359

SEE INSTRUCTION MANUAL
VOIR MANUEL
MFG MM-YY

Bayco Products, Inc. XPP-5414GX
640 S. Sanden Blvd., Wylie, TX 75098

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS

CLASS I DIV 1 GRPS A-D T3
CLASS II & III DIV 1 GRPS E-G T135ºC
CLASS I ZONE 0 AEx ia IIC T3 Ga
Ex ia IIC T3 Ga
Ⓔx II 1 G Ex ia op is IIC T3 Ga

Ex ia op is IIC T3 Ga
Intertek ITS 18 ATEX202366X
ITS21UKEX0268X
IECEx ITS 18.0005X
-20ºC ≤ Tamb ≤ +40ºC
1.5V/Cell with two
Energizer E91 or EN91

Meets the requirements of NFPA 1971-8.6 (2013)

ITEM NUMBER/UPC
- XPP-5414GX (light only) 0 17398 80664 0
- XPP-5414GX-KO1 (light with mount) 0 17398 80665 7
- NS-HMC7 (mount only) 0 17398 80666 4

MARKET APPLICATIONS
- Hazardous work environments, industrial, fire & rescue

CERTIFICATIONS
- CLASS I DIV 1: GRPS A-D T3
- CLASS II & III DIV 1: GRPS E-G T135°C
- CLASS I ZONE 0: Ex ia IIC T3 Ga
- ATEX Certification: II 1 G Ex ia op is IIC T3 Ga
- IECEx Certification: Ex ia op is IIC T3 Ga

CASE MATERIAL
- Engineered polymer

LUMENS/RUNTIME
FLASHLIGHT
- 120L, 24 hrs. runtime

FLOODLIGHT
- 120L, 24 hrs. runtime

DUAL-LIGHT
- 120L, 24 hrs. runtime

CANDELA
- 3,100

BEAM DISTANCE
- 111 m

WATER RATING
- ANSI IP-67 dustproof / waterproof

DROP RATING
- 2 meters

DIMENSIONS
- LENGTH: 6.25 in (159 mm)
- HANDLE DIAMETER: 0.86 in (22 mm)
- HEAD DIAMETER: 1.28 in (33 mm)
- WEIGHT: 4.1 oz (116 g)

POWER SOURCE
- AA batteries (not included)

WARRANTY
- Limited lifetime

WHAT'S INCLUDED

XPP-5414GX
- Flashlight
- Removable/Reversible Clip
- Instruction manual

XPP-5414GX-K01
- Flashlight
- NS-HMC7 multi-angle mount
- Removable/Reversible Clip
- Instruction manual

CERTIFIED

CE | IECEx | Ex | Intertek | NFPA | UK CA 0359

© 2023 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates. XPP-5414-23