

XPP-5418GX-K01 • XPP-5418RX-K01

X-Series Intrinsically Safe Flashlight w/ Multi-Angle Mount

MARKET APPLICATIONS

Hazardous work environments, industrial, automotive, fire and rescue

DESCRIPTION

This Flashlight is cETLus, ATEX, and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present. Uses a CREE® LED rated at 200 lumens that works with a deep parabolic reflector to create a 143 meter flashlight beam. The tail switch provides momentary or constant-on functionality. Meets the requirements of NFPA-1971-8.6. Power comes from 3 AA premium batteries (not included). The mount can be attached to either side of the helmet to provide hands-free illumination for the wearer. Additionally, the user can set the angle of the mount through 140 degrees of adjustment to provide clearance around face shields, goggles or other helmet-mounted equipment.

CASE MATERIAL

Glass-Filled Nylon Polymer

DIMENSIONS

Length 5.6 in. • Head Diameter 1.5 in. • Handle Diameter .75 x 1.4 in.

WEIGHT

5.4 oz.

LIGHT SOURCE

CREE® LED technology – 50,000 + hours LED life

LIGHT OUTPUT

Flashlight Lumens: 200

ON/OFF

Tailswitch. Momentary and constant on/off

RUN-TIME

10.5 hrs.

BATTERY

3 AA Batteries (not included)

FEATURES

- cETLus, ATEX, and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present
- Sharp focused flashlight beam for distance illumination
- Non-slip grip
- Mount can be attached to either side of helmet
- Mount allows for clearance around face shields, goggles or other helmet-mounted equipment.
- Dustproof / Waterproof
- Impact and chemical resistant
- Meets Requirements of NFPA-1971-8.6 (2013)

WARRANTY

Limited Lifetime Warranty

APPROVALS



 E 467756 INTRINSICALLY SAFE SECURITE INTRINSEQUE 	Bayco Products, Inc. XPP-5418GX/RX 640 S. Sanden Blvd., Wylie, TX 75098 Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS CLASS I DIV 1 GRPS A-D T3 CLASS II & III DIV 1 GRPS E-G T135°C CLASS I ZONE 0 AEx ia IIC T3 Ga Ex ia IIC T3 Ga Ⓢ II 1 G Ex ia op is IIC T3 Ga	Ex ia op is IIC T3 Ga Intertek ITS 13 ATEX27837X IECEx ITS 16.0067X -20°C ≤ Tamb ≤ +40°C 1.5V/Cell with three in series Energizer E91 or EN91
	<p>WARNINGS: Replace batteries in a non-hazardous location. Use only Energizer AA Model E91 or EN91 batteries.</p> <p>AVERTISSEMENT: Remplacer les piles dans une zone non dangereuse. Utiliser uniquement les piles Energizer AA - modèle E91 ou EN91.</p>	

