

3 AA BATTERIES

XPP-5422B, XPP-5422G

INTRINSICALLY SAFE DUAL-LIGHT FLASHLIGHT



DUAL-LIGHT


260-lumen Dual-Light provides simultaneous **flashlight and floodlight** operation



XPP-5422G



Simultaneous **flashlight and floodlight** operation



Sharp focused flashlight beam



Durable polymer body is **impact & chemical resistant**



Large, textured buttons



AVAILABLE IN MULTIPLE COLORS

XPP-5422B



260 LUMENS

1-800-233-2155 · 1-469-326-9400 · nightstick.com

INTRINSICALLY SAFE DUAL-LIGHT FLASHLIGHT

3 AA BATTERIES (not included)

ITEM NUMBER/UPC

- XPP-5422B, UPC 0 1739880094 5
- XPP-5422G, UPC 0 1739880093 8

MARKET APPLICATIONS

- Hazardous work environments, industrial, fire and rescue

CERTIFICATIONS

- ETLus, CE, UKCA, MSHA

CASE MATERIAL

- Engineered polymer

LUMENS/RUNTIME

FLASHLIGHT

- 160L, 19 hrs. runtime

FLOODLIGHT

- 130L, 19 hrs. runtime

DUAL-LIGHT

- 260L, 4.5 hrs. runtime

CANDELA

- 7,250

BEAM DISTANCE

- 170 m

WATER RATING

- ANSI IP-67 dustproof / waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 7.0 in (178 mm)
- HANDLE DIAMETER: 1.1 in x 1.5 in (28 mm x 38 mm)
- HEAD DIAMETER: 1.8 in (46 mm)
- WEIGHT: 6.9 oz (196 g)

POWER SOURCE

- AA batteries (not included)

WARRANTY

- Limited lifetime

WHAT'S INCLUDED

- Flashlight
- Removable lanyard
- Instruction manual

FL 1 STANDARD	FLASH	FLOOD	DUAL-LIGHT
	160 LUMENS	130 LUMENS	260 LUMENS
	19h	19h	4h 30min
	170m		
	7250cd		
	2m		
			1m

Bayco Products, Inc. XPP-5422B
640 S. Sanden Blvd.
Wylie, TX 75098

Permissible Nightstick 5422 Flashlight



APPROVAL No. 20-A130001-0

TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY

- WARNINGS:
- 1) MSHA approved for use with three AA Duracell Type PC1500, Energizer Type EN91, and Energizer Type L91 batteries only.
 - 2) Replace the batteries in fresh air only and replace all batteries at the same time. Do not mix batteries from different manufacturers or of different types.
 - 3) Energizer Lithium (Type L91) batteries are to be replaced by a qualified technician only.
 - 4) The Model Nightstick 5422 must not be opened in areas where permissibility is required.



Intertek
 ID 4003544
 INTRINSICALLY SAFE
 SECURITE INTRINSEQUE



CLASS I DIV 1 GRPS A-D T3
 CLASS II & III DIV 1 GRPS E-G T135C
 CLASS II ZONE 0 IIC T3
 CLASS II ZONE 20 IIC T135C
 -20°C ≤ Tamb ≤ +40°C
 1.5V/Cell AA Alkaline

CERTIFIED

