

RECHARGEABLE

INTRINSICALLY SAFE DUAL-LIGHT FLASHLIGHT

XPR-5522GMX

**NIGHTSTICK**  
Life Depends on Light™



## DUAL SWITCHES

Easily operate **independent flashlight and floodlight**, or simultaneous in Dual Light mode.

## MAGNETS

Rare earth magnets in the tail and on the pocket clip **provide hands-free operation.**



The **soft, unfocused floodlight** is integrated into the housing, perfect for close-up illumination.



**Dual body switches** are perfectly placed for easy one-handed operation, even with gloves.



**Integrated magnets in handle base and the pocket clip** provide options for limitless hands-free usage.

FL1 STANDARD	FLASH	FLOOD	DUAL-LIGHT
	240 LUMENS	175 LUMENS	400 LUMENS
	8h	8h 30min	4h 45min
	178m		
	7964cd		

400 LUMENS



1-800-233-2155 • 1-469-326-9400 • [nightstick.com](http://nightstick.com)

© 2024 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit [nightstick.com](http://nightstick.com) for product updates.

# DUAL-LIGHT FLASHLIGHT

## RECHARGEABLE

### ITEM NUMBER/UPC

XPR-5522GMX - 017398805643

### CERTIFICATIONS

- CE, cETLus, ATEX, IECEX, MSHA, KOSHA, UKCA, INMETRO

### CASE MATERIAL

- ABS polymer

### LUMENS/RUNTIME

#### SPOTLIGHT

- HIGH: 240L, 8 hrs. runtime

#### FLOODLIGHT

- HIGH: 175L, 8.5 hrs. runtime

#### DUAL-LIGHT

- HIGH: 400L, 4.75 hrs. runtime

### CANDELA

- HIGH: 7,964

### BEAM DISTANCE

- HIGH: 178m

### WATER RATING

- IP-67 (dustproof, waterproof)

### DROP RATING

- 2 meters

### DIMENSIONS

- LENGTH: 7.4 in (188mm)
- WIDTH: 1.7 in X 1.3 in (33mm x 43mm)
- BEZEL DIAMETER: 2.1 in (53mm)
- WEIGHT: 9.9 oz (280g)

### BATTERY







- Integrated Li-ion battery (included)

### WARRANTY

- Limited lifetime warranty

### WHAT'S INCLUDED

- Light with battery
- Lanyard
- Charger
- AC & DC cords

FL 1 STANDARD	FLASH	FLOOD	DUAL-LIGHT
	<b>240</b> LUMENS	<b>175</b> LUMENS	<b>400</b> LUMENS
	<b>8h</b>	<b>8h 30min</b>	<b>4h 45min</b>
	<b>178m</b>		
	<b>7964cd</b>		
			
			

Bayco Products, Inc.  
640 S. Sanden Blvd.  
Wylie, TX 75098

Model XPR-5522GMX Safety Flashlight  
Permissible Flashlight Assembly



APPROVAL No. 20-A160002-0

TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY

WARNINGS: 1) MSHA approved for use with one part number 5522-BATT rechargeable battery pack only.  
2) The Model XPR-5522GMX Safety Flashlight is only to be charged on the surface, or underground in accordance with the applicable regulations pertaining to battery-charging stations (reference 30 CFR 75.340) with a Bayco Products, Inc. model 5522-CHGR1.  
3) Do not open in areas where permissibility is required.

ATENÇÃO - UTILIZAR SOMENTE BATERIAS 5522-BATT.  
ATENÇÃO - NÃO SUBSTITUIR A BATERIA QUANDO UMA ATMOSFERA EXPLOSIVA PUDE ESTAR PRESENTE.  
ATENÇÃO - NÃO RECARREGUE A BATERIA EM ÁREAS CLASSIFICADAS.



CLASS I DIV 1 GRPS A-D T3  
CLASS II DIV 1 GRPS E-G Class III T200°C  
CLASS I ZONE 0 AEx ia IIC T3 Ga  
CLASS II ZONE 20 GRP IIC  
CLASS III 1 G Ex ia op is IIC T3 Ga

INTRINSICALLY SAFE Ex ia op is IIC T3 Ga

SECURITE INTRINSEQUE

INTERTEK ITS 16 ATEX201022X  
ITS21LUKEX0267X  
IECEX ITS 16.0045X  
-10°C ≤ Tamb ≤ +40°C IP54  
3.7V/Cell  
Input entity parameters for charging contacts on flashlight:  
U: 4.75V  
I: 500mA  
P: 0.59W  
C: 0.0uF

22-AV480-0248X

CE 2575 UK CA 0359

CS

INMETRO

CERTIFIED	CE	ETL	Ex	IECEX	CS	UK	CA	INMETRO
		Intertek				0359		