



# IECEX Certificate of Conformity

## INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit [www.iecex.com](http://www.iecex.com)

Certificate No.: **IECEX EPS 25.0013X**

Page 1 of 3

Certificate history:

Status: **Current**

Issue No: 0

Date of Issue: 2025-07-22

Applicant: **i.safe MOBILE GmbH**  
i\_Park Tauberfranken 10  
97922 Lauda-Koenigshofen  
Germany

Equipment: **IS-TH2ER.1 intrinsically safe mobile Scanner**

Optional accessory:

Type of Protection: **intrinsic safety "i", optical radiation "op is"**

Marking: **Ex ib op is IIC T4 Gb**  
**Ex ib op is IIIC T135°C Db**

Approved for issue on behalf of the IECEx  
Certification Body:

Position:

Signature:  
(for printed version)

Date:  
(for printed version)



1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting [www.iecex.com](http://www.iecex.com) or use of this QR Code.



Certificate issued by:

**Bureau Veritas Consumer Products Services Germany GmbH**  
Businesspark A96  
86842 Türkheim  
Germany





# IECEx Certificate of Conformity

Certificate No.: **IECEx EPS 25.0013X**

Page 2 of 3

Date of issue: 2025-07-22

Issue No: 0

Manufacturer: **i.safe MOBILE GmbH**  
i\_Park Tauberfranken 10  
97922 Lauda-Koenigshofen  
**Germany**

Manufacturing  
locations:

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

## STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

**IEC 60079-0:2017** Explosive atmospheres - Part 0: Equipment - General requirements  
Edition:7.0

**IEC 60079-11:2023** Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"  
Edition:7.0

**IEC 60079-28:2015** Explosive atmospheres - Part 28: Protection of equipment and transmission systems using optical radiation  
Edition:2

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

## TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

[DE/EPS/ExTR25.0013/00](#)

Quality Assessment Report:

[DE/EPS/QAR12.0003/17](#)



# IECEx Certificate of Conformity

Certificate No.: **IECEx EPS 25.0013X**

Page 3 of 3

Date of issue: 2025-07-22

Issue No: 0

## **EQUIPMENT:**

Equipment and systems covered by this Certificate are as follows:

The intrinsically safe and rugged mobile scanner IS-TH2ER.1 has been designed for the use in explosion hazardous areas of zone 1 and 21. In combination with mobile communication devices, the multifunctional set enables quick and easy scanning of any 1D or 2D barcodes at close range or at distances of more than 12 meters. The green laser is highly visible.

## Electrical data:

The supply and interface connection of the IS-TH2ER.1 is carried out via the ISM interface of the compatible communication devices. The IS-TH2ER.1 is certified in combination with the IS540.1 or other mobile devices that comply with the connection parameters in accordance with document 1071AD04.

## **SPECIFIC CONDITIONS OF USE: YES as shown below:**

The 16-pin connector of the IS-TH2ER.1 may only be installed or removed from the ISM interface outside of potentially explosive areas.

The device must be protected from impacts with high impact energy, against excessive UV light emission and high electrostatic charge processes.

The permitted ambient temperature range is -20 °C to +55 °C.