XPP-5564RX/GX







Battery status indicator - green indicates full charge and glows red when battery is nearing low



270 lumen floodlight - wide illumination at precise 45° downward angle





Easy press switches, independently controlling **separate LEDS**



Spring loaded clip and V-ring securely hold tight to gear in any situation





AVAILABLE IN HI-VIZ GREEN.

280 LUMENS



4AA

ITEM NUMBER/UPC

XPP-5564RX (Red), 017398806275 XPP-5564GX (Green), 017398806268

MARKET APPLICATIONS

Hazardous work environments, fire, rescue, industrial and automotive

CERTIFICATIONS

- CE, cETLus, ATEX, IECEx, NFPA

CASE MATERIAL

- PC/ABS

LUMENS/RUNTIME

FLASHLIGHT

- HIGH: 250L, 6 hrs. runtime
- LOW: 110L, 18 hrs. runtime

FLOODLIGHT

- HIGH: 270L, 8.5 hrs. runtime
- LOW: 120L, 28 hrs. runtime

DUAL-LIGHT

- 280L, 5.5 hrs. runtime

CANDELA

FLASHLIGHT

- HIGH: 54,900
- LOW: 7,333

BEAM DISTANCE

FLASHLIGHT

- HIGH: 469m
- LOW: 171m

WATER RATING

- IP-67 (Dustproof and Waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 6.25 in (159 mm)
- WIDTH: 2.75 in (70 mm)
- DEPTH: 2.5 in (64 mm)
- HEAD DIAMETER: 2.75 in (70 mm)
- WEIGHT: 11 oz (312g with batteries)

BATTERY

- 4AA batteries (included)

WARRANTY

- Limited Lifetime Warranty

WHAT'S INCLUDED

- Angle light
- 4AA hatteries
- Instruction manual



