

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: IECEx UL 16.0154 Page 1 of 4 <u>Certificate history:</u>

Issue 0 (2016-11-28)

Status: Current Issue No: 1

Date of Issue: 2020-01-31

Applicant: Bayco Products, Inc.

640 S. Sanden Blvd. Wylie, TX 75098

United States of America

Equipment: Multifunction Flashlight - Nightstick XPR-5580*

Optional accessory:

Type of Protection: Intrinsic Safety "ia"

Marking: Ex ia IIC T4 Ga

-20°C to +40°C

Approved for issue on behalf of the IECEx

Certification Body:

Signature:

Position:

(for printed version)

Date: 2020-01-31

- 1. This certificate and schedule may only be reproduced in full.
- 2. This certificate is not transferable and remains the property of the issuing body.
- 3. The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.

Katy A. Holdredge

Senior Staff Engineer



Certificate issued by:

UL LLC 333 Pfingsten Road Northbrook IL 60062-2096 United States of America





Certificate No.: **IECEX UL 16.0154** Page 2 of 4

Date of issue: 2020-01-31 Issue No: 1

Manufacturer: Bayco Products, Inc.

640 S. Sanden Blvd. Wylie, TX 75098

United States of America

Additional manufacturing locations:

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS:

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2011 Explosive atmospheres - Part 0: General requirements

Edition:6.0

Edition:6.0

IEC 60079-11:2011 Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"

This Certificate does not indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Reports:

US/UL/ExTR16.0179/00 US/UL/ExTR16.0179/01

Quality Assessment Report:

GB/ITS/QAR13.0005/06



Certificate No.: IECEx UL 16.0154 Page 3 of 4

Date of issue: 2020-01-31 Issue No: 1

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

The Models Nightstick XPR-5580* is a multifunction flashlight that is portable, hand-held, containing several LEDs and is powered by a rechargeable Li-ion battery pack Part No. Nightstick 5500-BATT. The device is provided in either red or green, both with black color bezel, clear lens, black pushbuttons and black battery compartment screw covers.

Please see Annex for additional information.

SPECIFIC CONDITIONS OF USE: NO



Certificate No.: IECEx UL 16.0154 Page 4 of 4

Date of issue: 2020-01-31 Issue No: 1

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)

Issue 1: Manufacturer supplied documentation for an alternate component and a battery pack revision.

Annex:

Annex to IECEx UL 16.0154 Issue 1.pdf



Certificate No.: IECEx UL 16.0154

Issue No.: 1 Page 1 of 1

TYPE DESIGNATION

Model Nomenclature is as follows: Nightstick XPR-5580*

* – R for red enclosure material or G for green enclosure material

PARAMETERS RELATING TO THE SAFETY

Um = 4.75V

MARKING

Marking has to be readable and indelible; it has to include the following indications:



E 467756 ID 4003544 INTRINSICALLY SAFE

CLASS I DIV 1 GRPS A-D T4, CLASS II & III DIV 1 GRPS E-G, CLASS I ZONE 0 GRP IIC T4, CLASS II ZONE 20 IIIC T135°C

SECURITE INTRINSEQUE

II 1 G Ex ia IIC T4 Ga Ex ia IIC T4 Ga
DEMKO 16 ATEX 1796, IECEx UL 16.0154
-20°C ≤ Tamb ≤ +40°C, 3.7V/Cell 5500-BATT, U_m = 4.75V

⚠ SEE INSTRUCTION MANUAL VOIR LE MANUEL D'INSTRUCTIONS

Bayco Products, Inc. XPR-5580 Wylie, TX 75098

C€2575

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS UL listed for use with Bayco Li-ion Battery Pack 5500-BATT