

LI-ION RECHARGEABLE

INTRINSICALLY SAFE DUAL-LIGHT™ CAP LAMP

XPR-5561G

NIGHTSTICK®

Life Depends on Light™

5 SETTINGS

INCLUDING HIGH & LOW

FEATURING
PULSE MODE

Automatic low
battery alert



Chemical, impact and IP-67 waterproof/dustproof for use in extreme environments



108 METERS

PRECISE FOCUSED BEAM



Get a **life-saving 247 hours of floodlight runtime** in Survival Mode (floodlight low setting)



The durable **integrated stainless-steel clip** attaches to virtually any helmet

FL 1 STANDARD	HIGH	LOW
	90 LUMENS	65 LUMENS
	13h	20h
	108m	58m
	5500cd	1571cd
	2m	1m

140 LUMENS



1-800-233-2155 · 1-469-326-9400 · nightstick.com

© 2019 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

INTRINSICALLY SAFE

DUAL-LIGHT™ CAP LAMP

LI-ION RECHARGEABLE

ITEM NUMBER/UPC

- XPR-5561G, 017398806718
(Light with Li-ion charger included)
- XPR-5561GC, 017398806916
(Light with helmet mount (NS-HMC9) and charger included)
- XPR-5561GLB, 017398806725
(Light and Li-ion battery only)

CERTIFICATIONS

- CE, cULus, ATEX, IECEx, MSHA

CASE MATERIAL

- Glass filled nylon polymer

LUMENS/RUNTIME

- SPOTLIGHT**
 - HIGH: 90L, 13 hrs. runtime
 - LOW: 65L, 20 hrs. runtime

FLOODLIGHT

- HIGH: 70L, 12 hrs. runtime
- LOW: 5L, 247 hrs. runtime

DUAL-LIGHT

- 140L, 9 hrs. runtime

CANDELA

- SPOTLIGHT**
 - HIGH: 5500
 - LOW: 1571

BEAM DISTANCE

- SPOTLIGHT**
 - HIGH: 108m
 - LOW: 58m

WATER RATING

- IP-67 (dustproof and waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 3.46 in (88mm)
- WIDTH: 1.35 in (34mm)
- DEPTH: 2.43 in (62mm)
- HEAD DIAMETER: 2.35 in (60mm)
- WEIGHT: 6.0 oz (170g)

BATTERY

- Rechargeable Li-ion battery

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- XPR-5561G
 - Light with Li-ion battery
 - Charger
 - AC/DC cord
- XPR-5561GC
 - Light with Li-ion battery
 - NS-HMC9 helmet mount
 - AC/DC cord
 - Charger
- XPR-5561GLB
 - Light with Li-ion battery

FL 1 STANDARD	HIGH	LOW
	90 LUMENS	65 LUMENS
	13h	20h
	108m	58m
	5500cd	1571cd

Bayco Products, Inc.
640 S. Sanden Blvd., Wylie, TX 75098

Model XPR-5561 Permissible Cap Lamp Assembly

MSHA APPROVAL No. 19-A160003-1
TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY

WARNINGS:
1) Only to be charged on the surface, or underground in accordance with the applicable regulations pertaining to battery-charging stations (reference 30 CFR 75.340) with a Bayco Products, Inc. Model 5560-CHGR2
2) Do not open in areas where permissibility is required.

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS
UL listed for use with Bayco Li-ion Battery Pack 5560-BATT

UL LISTED
E 467756
ID 4002026

CLASS I DIV 1 GRPS A-D T4 Ex ia I Ma
CLASS II & III DIV1 GRPS E-G T135°C Ex ia IIC T4 Ga
CLASS I ZONE 0 AEx ia IIC T4 Ga IECEx UL 17.0005
● II 1 G Ex ia I Ma -20°C ≤ Tamb ≤ +40°C
● II 1 G Ex ia IIC T4 Ga 3.7V/Cell Li-ion Um: 10V

INTRINSICALLY SAFE
SECURITE INTRINSEQUE

CE 0359

WARNING: Do not charge battery in a hazardous location
WARNING: Do not replace battery when an explosive atmosphere is present

CERTIFIED

MSHA

© 2019 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates. XPR-5561G-Series-19

